

MXY2

SEEDER FOR
FINE GRAIN . PASTURES
COARSE GRAIN



RELIABILITY . ADAPTABILITY . VERYGOODSOWING



AGROMETAL

“ Maintenance-free seeding unit built with fully armored bearings. Without lubrication points in the unit. ”



FEATURES

- » High resistance tubular chassis
- » Average weight per line 295 kg (****)
- » Pull along transportation system (3.9 mts in trailer)
- » Hydraulic drawbar
- » Compensated hydraulic lifting
- » Hydraulic rear loading outlet
- » Single hopper for seed and fertilizer
- » Volumetric seed meter for a wide range of sizes
 - Double opening pulley
 - New generation mechanical horizontal plate (*)
 - Helicoidal rotor system for lucerne seed
- » Chevron-type fertilizer meter
- » Transmission system
 - Electric/hydraulic (*)
 - Mechanic
 - -81 gear system for seed
 - -27 gear system for fertilizer
 - -27 gear system for lucerne
- » Lubrication free tilling system
- » DIRECTA 18" cutting coulter
- » Lubrication free seeding system (****)
- » 16" double planting disc blades
- » Seeding units suitable for heavy soils (*)
- » Pressure adjustment on seeding units
- » Double leveling wheel to adjust depth
- » Locking angle regulation
- » Seed firmer

Optional

- » Coarse grain kit with horizontal plate mechanical seed meter for single grain seeding at 35 cm or 42 cm according to the model.
- » Single hopper
 - One hopper
 - Maximum autonomy
- » Press wheels
 - Smelting 16 mm x 13" trapezoid section
 - Serrated supplement for smelting covers.
- » Seeding controllers
 - Controller
 - Computer
 - DVA system hydraulic variable seed metering.
 - Lucerne seed.

(*) Opcional

(**) The figures are illustrative and they depend on the model, the optional features, and the characteristics of the ground where the machine is going to work like the relief of the land, the texture, etc.

(***) Except horizontal plate seed meter.

(****) It may vary according to model.

MXV II Technical Specifications

Hopper capacity

| X MODEL | X SPACING | | X SINGLE HOPPER | | | X MAXIMUM AUTONOMY | | | X LUCERNE SEED | | X POWER (**) |
|--|---------------|--------------|-----------------|------------|-----------|--------------------|------------|-----------|----------------|---------------|---------------|
| | FINE GRAIN | COARSE GRAIN | SEED | FERTILIZER | SEED ONLY | SEED | FERTILIZER | SEED ONLY | SINGLE HOPPER | MAX. AUTONOMY | |
| 1 MODULE (BETWEEN ROWS 17,5 / 21CM) | | | | | | | | | | | |
| 2321 | 23 AT 21 CM | 12 AT 42 CM | 914 LTS | 609 LTS | 1325 LTS | 1828 LTS | 1218 LTS | 2650 LTS | 214 LTS | 428 LTS | 105 TO 140 HP |
| 2717 | 27 AT 17,5 CM | 14 AT 35 CM | 914 LTS | 609 LTS | 1325 LTS | 1828 LTS | 1218 LTS | 2650 LTS | 214 LTS | 428 LTS | 125 TO 160 HP |
| 3321 | 33 AT 21 CM | 16 AT 35 CM | 1211 LTS | 807 LTS | 1755 LTS | 2422 LTS | 1614 LTS | 3510 LTS | 283 LTS | 566 LTS | 150 TO 200 HP |
| 3717 | 37 AT 17,5 CM | 18 AT 35 CM | 1211 LTS | 807 LTS | 1755 LTS | 2422 LTS | 1614 LTS | 3510 LTS | 283 LTS | 566 LTS | 170 TO 220 HP |
| 2 MODULE (BETWEEN ROWS 17,5 / 21CM) | | | | | | | | | | | |
| 4721 | 47 AT 21 CM | 24 AT 42 CM | 1828 LTS | 1281 LTS | 2650 LTS | 3656 LTS | 2436 LTS | 5300 LTS | 428 LTS | 856 LTS | 215 TO 285 HP |
| 5517 | 55 AT 17,5 CM | 28 AT 35 CM | - | - | - | 3656 LTS | 2436 LTS | 5300 LTS | - | 856 LTS | 250 TO 330 HP |



AGROMETAL

+54 3468 562008

- ventas@agrometal.com

- www.agrometal.com

